



Product Service

CERTIFICATE

No. Z2 18 06 68782 021

Holder of Certificate: **Wuhan Rixin Technology Co., Ltd.**

Building 2, PV Industrial Park,
 Wuhan Rixin Technology Co.,Ltd.
 No.6, Middle Maodianshan Road,
 Wuhan East Lake Development Zone,
 430073 Wuhan, Hubei
 PEOPLE'S REPUBLIC OF CHINA



Certification Mark:



Product:

**Crystalline Silicon Terrestrial Photovoltaic (PV) Modules
Mono-Crystalline Silicon Photovoltaic Module**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 704061624501-01

Valid until: 2023-06-06



Date, 2018-06-08

(Zhulin Zhang)

Page 1 of 3



CERTIFICATE

No. Z2 18 06 68782 021

Model(s):

DDG290, DDG295, DDG300, DDG305, DDG310,
 DDG315, DDG320, DDG325, DDG330, DDG335,
 DDG340, DDG345, DDG350, DDM245, DDM250,
 DDM255, DDM260, DDM265, DDM270,
 DDM275, DDM280, DDM285, DDM290,
 DDG(N)320, DDG(N)325, DDG(N)330, DDG(N)335,
 DDG(N)340, DDG(N)345, DDG(N)350, DDG(N)355,
 DDG(N)360, DDG(N)365, DDG(N)370, DDG(N)375,
 DDG(N)380, DDM(N)265, DDM(N)270, DDM(N)275,
 DDM(N)280, DDM(N)285, DDM(N)290, DDM(N)295,
 DDM(N)300, DDM(N)305, DDM(N)310, DDM(N)315,
 DDG(N)340, DDG(N)345, DDG(N)350, DDG(N)355,
 DDG(N)360, DDG(N)365, DDG(N)370, DDG(N)375,
 DDG(N)380, DDG(N)385, DDG(N)390, DDG(N)395,
 DDG(N)400, DDG(N)405, DDM(N)285, DDM(N)290,
 DDM(N)295, DDM(N)300, DDM(N)305, DDM(N)310,
 DDM(N)315, DDM(N)320, DDM(N)325, DDM(N)330,
 DDM(N)335, DDM(N)340.

Parameters:

Rated Output Power at STC:	See the attachment
Construction:	Frameless, with Junction box, Cable and Connectors.
Test Laboratory:	Yangzhou Opto-Electrical Products Testing Institute; No. 10 West Kaifa Road, Yangzhou, 225009 Jiangsu, P. R. China
Application Class:	Class A
Maximum System Voltage:	1500V DC
Fire Safety Class:	Class C

Tested according to:

IEC 61215(ed.2)
 IEC 61730-1(ed.1);am1;am2
 IEC 61730-2(ed.1);am1

Production Facility(ies):

68782, 93917

CERTIFICATE
No. Z2 18 06 68782 021



Product Service

The following models will be covered by above certificate:

All electrical data shown as below is based on standard test condition: Front side irradiance 1000 W/m ² , 25 °C, AM 1.5	
Model	Rated Output Power at STC
DDG290, DDG295, DDG300, DDG305, DDG310, DDG315, DDG320, DDG325, DDG330, DDG335, DDG340, DDG345, DDG350,	290 W, 295 W, 300 W, 305 W, 310 W, 315 W, 320 W, 325 W, 330 W, 335 W, 340 W, 345 W, 350 W,
DDM245, DDM250, DDM255, DDM260, DDM265, DDM270, DDM275, DDM280, DDM285, DDM290,	245 W, 250 W, 255 W, 260 W, 265 W, 270 W, 275 W, 280 W, 285 W, 290 W,
DDG(N)320, DDG(N)325, DDG(N)330, DDG(N)335, DDG(N)340, DDG(N)345, DDG(N)350, DDG(N)355, DDG(N)360, DDG(N)365, DDG(N)370, DDG(N)375, DDG(N)380,	320 W, 325 W, 330 W, 335 W, 340 W, 345 W, 350 W, 355 W, 360 W, 365 W, 370 W, 375 W, 380 W,
DDM(N)265, DDM(N)270, DDM(N)275, DM(N)280, DDM(N)285, DDM(N)290, DDM(N)295, DM(N)300, DDM(N)305, DDM(N)310, DDM(N)315,	265 W, 270 W, 275 W, 280 W, 285 W, 290 W, 295 W, 300 W, 305 W, 310 W, 315 W,
All electrical data shown as below is based on test condition: Front side irradiance 1000 W/m ² , backside irradiance 100 W/m ² , 25 °C, AM 1.5	
Model	Rated Output Power
DDG(N)340, DDG(N)345, DDG(N)350, DDG(N)355, DDG(N)360, DDG(N)365, DDG(N)370, DDG(N)375, DDG(N)380, DDG(N)385, DDG(N)390, DDG(N)395, DDG(N)400, DDG(N)405,	340 W, 345 W, 350 W, 355 W, 360 W, 365 W, 370 W, 375 W, 380 W, 385 W, 390 W, 395 W, 400 W, 405 W,
DDM(N)285, DDM(N)290, DDM(N)295, DDM(N)300, DDM(N)305, DDM(N)310, DDM(N)315, DDM(N)320, DDM(N)325, DDM(N)330, DDM(N)335, DDM(N)340.	285 W, 290 W, 295 W, 300 W, 305 W, 310 W, 315 W, 320 W, 325 W, 330 W, 335 W, 340 W.